Exile E2 AD Multi Point Deadlocks



High security locking for aluminum framed glass doors

Exile AD Multi Point Deadlocks provide maximum protection against forced entry for commercial aluminium framed doors. Available in 2 or 4 point, the AD range of locks are strong, simple to install and designed to give a trouble free service life. Available for the most popular wide stile sections.



High Strength

- Two large horizontal stainless steel lock bars (50 x 10mm) engage with the adjacent door frame
- Two additional vertical stainless steel locking bolts (16mm diameter) that engage with the door frame head and floor in the M4AD lock
- The lock assembly reinforces the door stile structure for added strength

High Security

- The lock is designed to ensure it remains engaged and deadlocked until released by lever activation
- The deadlocked bars prevent forced lock actuation
- External lever control isolation separates the lever mechanism from the lock until the key control link is engaged
- Remote electronic lock monitoring magnetically activates a door frame mounted sensor without requiring any electrical connection to the lock
- Compatible with most 570 oval cylinders

Self-Latching or Manual Engagement

- Self-latching automatically extends the lock bars when the door is closed
- Manual latching allows the lock operating lever to engage the lock bars after the door is closed
- Both configurations are interchangeable depending on application


Solid Structure

 Constructed from aluminium, 304G stainless steel, brass bushes and sealed bearings

Entrance/Egress or Egress only configurations

- Entrance/Egress configurations have lock control from both sides of the door
- Egress configurations have lever control from the lock side of the door only

Suited for wide aluminium door stiles with a lock pocket larger than 88mm(d) x 40mm(w)



E2M4AD Lock

